

geoliner 650 XD

IMAGING WHEEL
ALIGNMENT
SYSTEMS

High-resolution
imaging technology
delivers speed
and accuracy



geoliner 650 XD

Highly accurate wheel alignment systems


VERSATILE, ACCURATE HARDWARE

- High-resolution cameras produce accurate, live alignment readings and diagnostic data
- Advanced XD targets and AC100 clamps are lightweight, durable and impact resistant
- Passive front and rear XD targets improve durability with no electronics to damage

STANDARD DIMENSIONING AND PRODUCTIVITY FEATURES

- Vehicle track width and wheel base
- Individual wheel side set and set-back
- EZ-TOE* for adjusting without using the steering wheel holder
- Guided adjustments of single tie rod, drag link and cradle

*Patented and / or patent-pending features




The geoliner 650 XD wheel alignment system provides core features for the alignment professional

Patented imaging technology provides accurate and real-time measurements that improves productivity. User-friendly features such as EZ-TOE*, VODI* and an extensive vehicle specification database delivers customer satisfaction, ease of use and accuracy.



AC100 universal wheel clamps



FAST AND EASY TO USE

- Self-centring design for accurate measurement of vehicle dimensions
- Two-sided claws eliminate accessories and allow reliable clamping even over hub caps
- Accessories available to accommodate larger wheels

RIDE HEIGHT* MEASUREMENT

Manual ride height to obtain proper alignment specs for those vehicles requiring it

EZ-TOE*

Turn the front wheels and access difficult adjustment points while still displaying centred toe readings

USER-FRIENDLY INTERFACE

Use available step-by-step instructions as a guide for completing even the most complex tasks

MANUFACTURER SPECS

Extensive OEM specs allow quick and accurate vehicle selection

VODI™

Vehicle Orientation Directional Indicator* – guides the technician through the measurement process

HELP VIDEOS

View detailed videos of how to make needed adjustments to complete even the most complex task

*Patented and / or patent-pending features

Product features & specifications

OPTIONAL ACCESSORIES

- Drive-on camera aid: EAK0289J91A
- Hub adaptor kit for wheels-off alignment: 29215
- AC100 universal wheel clamp extension kit: 30926
- Dual tall support kit: EAK0289J80A
- Centre tall support kit: 4031236
- Dual short support kit: EAK0289J81A
- Centre short support kit: 4031234
- Tilt camera beam: 4031154
- TIP target: 4028515



SPECIFICATIONS

- Rim size: 11" – 22" (27.94 cm – 55.88 cm)
- Track width: 48" – 96" (122 cm – 244 cm)
- Wheel base: 79" – 180" (201 cm – 457 cm)
- Shipping weights: 501 lbs (227 kg)
- Power requirements: 120/230V 1 Ph 50/60Hz

AC100 SPECIFICATIONS

- Weight: 4.9 – 5.2 kg (10.9 – 11.5 lbs)
- Construction: Cast aluminium

STANDARD ACCESSORIES

- Wheel clamps & targets
- Steering wheel holder
- Brake pedal depressor
- Two wheel chocks
- Printer

EMEA-JA

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.hofmann-europe.com

France

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP 97175
Saint-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX
Phone: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.hofmann-france.fr

Germany

Snap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen
Phone: +49 8634 622-0 · Fax: +49 8634 5501 · www.hofmann-deutschland.com

Italy

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-410
www.hofmann-italia.com

United Kingdom

Snap-on Equipment Ltd. · Unit 17 Denney Road, King's Lynn · Norfolk PE30 4HG
Phone: +44 118 929-6811 · Fax: +44 118 966-4369
www.snapon-equipment.co.uk

