NitroRide®

Tyre Inflation Workstation

A good Combi

Nitrogen Generator WITH Automatic Inflation System







NR250AF ideal for Bikes/Cars/Caravans/ 4X4 and light truck tyres NR500AF ideal for Bikes/Cars/Caravans/ 4X4/Bus and large tyres

Nitrogen generator features and speifications

> Generates Nitrogen at a rate of
4380 Lts/Hr - NR250AF
12000 Lts/Hr - NR500AF

- > A large 84 Lts storage tank
- > 3 high grade filter separation system > Inlet/outlet pressure indicators along with a Filter Condition gauge

Model	NR250AF	NR500AF
Recommend input pressure	12 kgs/cm ²	14 kg/cm ²
Purity of Nitrogen	95-99.5%	95-99.5%
Storage tank size	84 Lts	84 Lts
Output Pressure	12 kgs/cm ²	12 kgs/cm ²
Nitrogen capacity	73Lts/Min	200Lts/Min
Dimensions	650X360X1320mm	520X300X1220mm
Weight	82Kgs	99Kgs





Model



Automatic inflation features and specifications

- * Two large LED displays, preset pressure, acture pressure.
- * Self-calibrating fault diagnostics every time you switch on.
- * Sleep mode when not being used.
- * Reads in both PSI and Bar.
- * Auto stops with an audible sound when the procedure is completed or if a pribem occures.
- * Bead seating function, allows the tyre to be over inflated and then deflated to the pre-set pressure fully automatically.
- * The N2 option purges the tyre of Oxygen in preparation for filling with NITROGEN.
- * Auto inflates, for multiple tyre inflation.

Operating Temperature	-10 °C ∼ +50°C	
Supply Voltage	100-240V,50/60Hz,45W	
Display	8 digit LED	
Operating Principle	Microprocessor Digital Control	
Max. Inlet Air Supply	170 Psi (12 Bar)	230 Psi (16 Bar)
Min. Inlet Air Supply	5 Psi (0.3 Bar)	
Operating Pressure Range	$3~\sim 150~{ m Psi}$	$3\sim 200~\text{Psi}$
	(0.2 \sim 10.5 Bar)	(0.2 \sim 14 Bar)
Precision	1 Psi	
Units of Measurement	Psi, Bar	
Bead Seating	0-100% Over-inflation of Target Pressure	
N2 function	1-5 variable purge cycles with variable deflation threshold (15% to 30%)	
Automatic inflation	Skip pressing START button for multiple tyre inflation. Variable pre-sets.	

NR250AF

Please contact our distributor :



166, Wyckham Road, Castle Browmich, Birmingham B36 0HU England Tel: +44 (0)121 748 4954 Website : www.jia-sources.com

Fax: +44 (0)121 240 5218 Email: info@jia-sources.com

NR500AF