

PRO-CUT

ON-CAR BRAKE LATHES



The all new 2008
PFM 9.2
Perfect brake job. Every time.

- 1 ALL NEW DRO!
Constant "Live" runout readings to show and confirm lathe accuracy!
- 2 DISK-LOCK TROLLEY
Disc lock system with dual sealed bearings allow zero gravity movement with full lock-down capability.
- 3 SPEED-LOCK CUTTING HEAD
All new cutting head can be moved and set with one hand!



PFM 9.2 ON CAR BRAKE LATHE ▶

Any car. Any lift. 7-9 minutes per rotor!

"We do a tremendous amount of brake work, and my technicians liked the first one so well that I had to purchase an additional one just to keep up with the demand. I would highly recommend this investment to any service facility; it will pay for itself in no time at all!"

-Mike Frazier
Adams Motor Company, Lynchburg, VA

PFM 9.2

Perfect brake job. Every time.

1 2, 5 AND 7 ADAPTER PACKAGES AVAILABLE.

The 2 Adapter Package gets you on most 4/5 lug cars, while the 5 Adapter Package gets you 4/5 lug cars + most half-ton trucks. Stepping up to the 7 Adapter Package gives you everything plus the standard 3/4 and 1 ton truck adapters.

2 New DRO(Digital Run-Out) "Live"!

Every new PFM 9.2 now comes with a precision matched on-board rate sensor and a "Live" digital run-out display to increase accuracy and help verify that you get a "Perfect Brake Job. Every Time!" DRO also includes ROI tracking capability to validate your investment!

3 CUSTOMIZE YOUR COMPLETE KIT.

Have a shop that is brand or lift specific? No problem! Work with your Pro-Cut Representative to custom build the adapter and trolley package that works best for you.

4 FREE ON-SITE DEMO. GIVE US A CALL.

Still not convinced about the Pro-Cut? Call our toll free number, **1-800-543-6618** and we'll set up a free on-site demo so you can get hands on with the Pro-Cut with no obligations.



ESSENTIAL EQUIPMENT
PRO-CUT
OEM RECOMMENDED

OEM ESSENTIAL EQUIPMENT

CHEVROLET, GMC, NISSAN, INFINITI, FORD, LINCOLN-MERCURY, SUBARU

APPROVED / RECOMMENDED

TOYOTA, LEXUS, CHRYSLER, DODGE, JEEP, VW, BMW, HYUNDAI, MAZDA, ISUZU

SPECIFICATIONS:

Maximum Rotor Thickness:	1.75"
Minimum Rotor Thickness:	0.2"
Maximum Rotor Diameter:	17.2"
Minimum Rotor Diameter:	4"
Maximum Depth of Cut:	0.020" / side
Spindle Speed:	123 RPM

Carriage Speed:	0.005" / rev.
Motor:	1.00 HP
Weight:	90 lbs.
Electrical Supply:	120v/1ph/60hz
Shipping Weight:	200 lbs.

THIS SYSTEM IS SUBJECT TO ONE OR MORE OF U.S. PATENTS: 6,050,160 / 6,101,911 / 6,216,571 / 6,327,947 / 6,330,847 / 6,474,203 / 6,477,928 / 6,895,851 / 5,974,878

10 TECHNOLOGY DRIVE, #4 WEST LEBANON, NH 03784 USA | P. 800.543.6618 / F. 603.298.8404 | INFO@PROCUTUSA.COM | WWW.PROCUTUSA.COM