

*monty® 3300-22 2-speed*



**High-versatility  
tyre changer**

## monty® 3300-22 2-speed

Speed Plus is the new advanced multi-speed drive technology. The slow speed is ideally suited for accurate and attentive operation in critical phases e.g. when dealing with difficult tyre beads, whereas quick speed allows to save time in uncritical phases.



- The machines are equipped with a three-position adjustable bead breaker, operated by a double acting cylinder and an oversize bead breaker blade which prevent damage to tyre and rim.
- Alloy rims are handled particularly gently as the mounting head and the clamping jaws are provided with plastic protectors.
- The pneumatic tilt-back post and the four ergonomic pedals stand for user-friendly operation.



- Accurate and quick operation is guaranteed owing to the self-centring four-jaw turntable controlled by two clamping cylinders and the exactly locked post.
- The tyre inflator is operated by pedal, equipped with a quick inflation valve and a pressure gauge mounted on the tower. The machine is also available as monty 3300-22 2-speed GP with top-side bead seating kit.
- Equipped with easymont pro and the plus kit the machine is available as monty 3300-22 2-speed plus for handling of UHP and run-flat tyres, hence certified according to wdk requirements. Easymont pro is also available as optional accessory.
- This tyre changer is also available in single-speed version as monty 3300-22 without Speed Plus technology and without various other components and features.

Technical data*		monty 3300-22	monty 3300-22 2-speed
Clamping range	inch	outer: 10 – 22 / inner: 12 – 24	outer: 10 – 22 / inner: 12 – 24
Max. rim width	inch	3 – 12	3 – 12
Max. tyre width	inch	13	13
Max. wheel diameter	mm	1000	1000
Bead breaking range	mm	30 – 340	40 – 392
Turntable speed	rpm	CW 8 / CCW 8	CW 7-14 / CCW 7
Max. rotation torque	Nm	1020	1200
Compressed air supply	bar	8 – 12	8 – 12
Dimensions (W x D x H)	mm	1300 x 1700 x 1860	1300 x 1700 x 1860
Weight	kg	220	220
Power supply		400 VAC 3ph 50 Hz	230 VAC 1ph 50 – 60 Hz

\* Specification based on OEM tyres

**Snap-on** EQUIPMENT

#### EMEA-JA

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)  
Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.snapon-equipment.eu

#### France

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP 97175  
Saint-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX  
Phone: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.snapon-equipment.fr

#### Germany

Snap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen  
Phone: +49 8634 622-0 · Fax: +49 8634 5501 · www.snapon-equipment.de

#### Italy

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)  
Phone: +39 0522 733-411 · Fax: +39 0522 733-410  
www.snapon-equipment.eu

#### United Kingdom

Snap-on Equipment Ltd. · 48 Sutton Park Avenue · Reading RG6 1AZ  
Phone: +44 118 929-6811 · Fax: +44 118 966-4369  
www.snapon-equipment.co.uk

